

1 (12)

APPLICATION AND REPORT FORM FOR THE ATPL(A) SKILL TEST, TYPE RATING SKILL TEST AND PROFICIENCY CHECKS ON MUL AEROPLANES AND SINGLE PILOT COMPLEX AEROPLANES WITH HIGH PERFORMANCE ACCORDING TO APPENDIX 9 TO COMM	
REGULATION (EU) NO 1178/2011 OF 3 NOVEMBER 2011	1991014

<b>A</b> .	Skill test ATPL		B. to be completed by		Date of test		
	Skill test type rating			niner			
	PC Revalidation				Licence e	endorsement (type of aircraft)	
	PC Renewal						
	Multi pilot aeroplane		Applicant tested	as:	lf test pe	erformed in aircraft	
	Single pilot aeroplane (	SPO)					
	Single pilot aeroplane (I	MPO)			Registra	tion	
C. To be	Date of birth (yyyy-mm-dd)		State of licence iss		Licence n	0	
completed by	Last name			First and middle nam	es		
the applicant	Street or box			Country		Telephone	
	Postal code and city			E-mail address			
	Total flight time	Total tir	me as PIC/PICUS /	Instrument time/Grou /	nd time	FFS/FNPT /	
	Total time MPA	Cross-c	country PIC/PICUS Night flight			PICUS verification attachment	
	Applicant verification of c	omplianc	ce according to ARA.	GEN.315 and AMC1 A	RA.GEN.31	5 (c) (See instructions, page 10)	
D. To be	TRAINING COMPLET	ED AN	ID APPLICATI		)		
completed by	Name of ATO		Date				
the ATO	Flight time during course		Total time in FS/FFS during course FTD: FFS:			se	
	Refresher training comp	leted	Attending ZF	TT course	Approved for PC renewal		
	Recommendation by Head of Tra nominated by the Head of Trainir		other person	Name in block letters			
	Result of the test						
E. To be completed by	If 1-5 iter	ns are f		– Final resul – Final resul – Final resul	t : Partial	-	
the examiner	Final result:	P	Passed	Partial pass		Failed	
			Tempora	ary rating issued			
				details in the appli	cant's lic		
	Rating	Date	e of test/check	Rating valid u	Intii	IR valid until	
	Examiner's certificate number:			Stamp/Printed name			
	Signature of examiner: can as PDF, send by e-mail to: (	ortifi	bat w3d2@two	nenorteturoleor	<b>. . . . .</b>	mail to.	

Scan as PDF, send by e-mail to: <u>certifikat.w3d3(*a*)transportstyrelsen.se</u> or by mail to Transportstyrelsen, SE-601 73 Norrköping Webbsida: <u>transportstyrelsen.se</u>



Before Test/check	Before PC, revalidation	Before ATPL Skill Test			
Before Test/check  Technical training (initial issue only) Valid or expired IR/ME (Initial issue only) AUPRT (certificate or verification attached when required, see page 10 section F) Valid CPL/MPL/ATPL licence Valid language proficiency Personal identification card In case of non-Swedish ATO, required documentation attached (see	∨alid type rating         Route Sectors ≥10 or         Examiner accompanied route sector         In case of non-Swedish examiner,         required documentation attached (see         page 10 section E)         Before PC, renewal         Approved training performed by	In case of non-Swedish examiner, required documentation attached (see page 10 section E)      All prerequisites checked, documented as required in section C and confirmed including latest revision of Examiners Differences			
page 10 section D)	ATO (Copy of course completion certificate must be attached)	EDD revision nr:			
	required documentation attached (see page 10 section E)	Examiner			

#### Before PBN test/check (initial)

Approved to be tested on PBN (BSL 14254 attached to this application if PBN privileges not confirmed in logbook or by other means)

Before test/check if PBN approach is not included in the test

Applicant has previously met PBN requirements (must be confirmed by logbook entry or operator statement)

ot Test to be performed  $\operatorname{not}$  including PBN approach, applicant informed of limitations in IR following a successful test.

M=Mandatory exercise or a choice where more than one exercise appears P=Trained as PIC or COP and as PF and PNF for issue X=FS only (see instructions) \*=Actual or simulated IMC P# = the training shall be complemented by supervised aeroplane inspection



G.

# ATPL (A) type rating multi-pilot (A) and single-pilot complex (A) high performance

SECT	ION 1 FLIGHT PREPARATION	FSTD	A	Instructors initials when training completed	Tested or checked in FSTD or A	Pass	Fail
1.1	Performance calculation	OTD P					
1.2	Aeroplane external visual inspection; location of each item and purpose of inspection	OTD P#	Р				
1.3	Cockpit inspection	P→	$\rightarrow$				
1.4	Use of checklist prior to starting engines, starting procedures, radio and navigation equipment check, selection and setting of navigation and communication frequencies	P→	→		м		
1.5	Taxiing in compliance with air traffic control or instructions of instructor	P→	$\rightarrow$				
1.6	Before take-off checks	P→	$\rightarrow$		м		
	-			Examiners initials when	11		

test section completed.....

SECTI	ON 2 TAKE-OFFS	FSTD	A	Instructors initials when training completed	Tested or checked in FSTD or A	Fail
2.1	Normal take offs with different flap settings, including expedited take off	P→	$\rightarrow$			
2.2*	Instrument take-off; transition to instrument flight is required during rotation or immediately after becoming airborne	P→	→			
2.3	Cross wind take-off (A, if practicable)	P→	$\rightarrow$			
2.4	Take-off at maximum takeoff mass (actual or simulated maximum take-off mass)	P→	$\rightarrow$			
2.5	Take-offs with simulated engine failure:	P>	>			
2.5.1*	- shortly after reaching V <sub>2</sub> (In aeroplanes which are not certificated as transport category aeroplanes (JAR/FAR 25) or as commuter category aeroplanes (SFAR 23), the engine failure shall not be simulated until reaching a minimum height of 500ft above runway end. In aeroplanes having the same performance as a transport category aeroplane regarding take-off mass and density altitude, the instructor may simulate the engine failure shortly after reaching V <sub>2</sub> .)	P→	→			
2.5.2*	- between V1 and V2	Р	x		M FFS Only	
2.6	Rejected take-off at a reasonable speed before reaching V1.	P→	$\rightarrow$		м	
				Examiners initials when test section completed		



-	DN 3 FLIGHT MANEUVRES	FSTD	<	Instructors initials when training completed	Tested or checked in FSTD or A	Pass	Fail
3.1	Manual flight with and without flight directors (no autopilot, no auto thrust/auto throttle, and at different control laws, where applicable)	P→	$\rightarrow$				
3.1.1	At different speeds (including slow flight) and altitudes within the FSTD training envelope	P→	$\rightarrow$				
3.1.2	Steep turns using 45° bank, 180° to 360° left and right	P→	$\rightarrow$				
3.1.3	Turns with and without Spoilers	P→	$\rightarrow$				
3.1.4	Procedural instrument flying and manoeuvring including instrument departure and arrival, and visual approach	P→	$\rightarrow$				
3.2	Tuck under and Mach buffets after reaching the critical Mach number, and other specific flight characteristics of the aeroplane (e.g. Dutch Roll)	P→	→x An aircraft may not be used for this exercise				
3.3	Normal operation of systems and controls engineer's panel	OTD→	$\rightarrow$				
<b>operat</b> i (A man	mal and abnormal tons of following systems: datory minimum of 3 items shall cted from 3.4.0 to 3.4.14 e)				М		
3.4.0	Engine (if necessary propeller)	$OTD \rightarrow$	$\rightarrow$				
3.4.1	Pressurisation and airconditioning	$OTD \rightarrow$	$\rightarrow$				
3.4.2	Pitot/static system	$OTD \rightarrow$	$\rightarrow$				
3.4.3	Fuel system	$OTD \rightarrow$	$\rightarrow$				
3.4.4	Electrical system	$OTD \rightarrow$	$\rightarrow$				
	Hydraulic system	$OTD \rightarrow$	$\rightarrow$				
3.4.6	Flight control and trim system	$OTD \rightarrow$	$\rightarrow$				
3.4.7	Anti- and de-icing system, Glare shield heating	$OTD \rightarrow$	$\rightarrow$				
3.4.8	Autopilot/Flight director	$OTD \rightarrow$	$\rightarrow$		<b>M</b> (single pilot only)		
3.4.9	augmentation devices	$OTD \rightarrow$	$\rightarrow$				
3.4.10	Ground proximity warning system Weather radar, radio altimeter, transponder	P→	$\rightarrow$				
3.4.11	Radios, navigation equipment, instruments, flight management system	$OTD \rightarrow$	$\rightarrow$				
3.4.12	Landing gear and brake	OTD P →	$\rightarrow$				
3.4.13	Slat and flap system	$OTD \rightarrow$	$\rightarrow$				
3.4.14	Auxiliary power unit	OTD P →	$\rightarrow$				
	Intentionally left blank						



proced items sl 3.6.9 in	<b>normal and emergency</b> <b>ures:</b> A mandatory minimum of 3 nall be selected from 3.6.1 to clusive.				М	
3.6.1	Fire drills e.g. Engine, APU, cabin, cargo compartment, flight deck, wing and electrical fires including evacuation.	P→	$\rightarrow$			
3.6.2	Smoke control and removal	P→	$\rightarrow$			
3.6.3	Engine failures, shut-down and restart at a safe height	P→	$\rightarrow$			
3.6.4	Fuel dumping (simulated)	P→	$\rightarrow$			
3.6.5	Wind shear at Take off/ Landing	Р	x		FFS only	
3.6.6	Simulated cabin pressure failure/Emergency descent	P→	$\rightarrow$			
3.6.7	Incapacitation of flight crew Member	P→	$\rightarrow$			
3.6.8	Other emergency procedures as outlined in the appropriate aeroplane Flight Manual	→	→			
3.6.9	TCAS event	OTD P→	x		FFS only	
3.7	Upset recovery training	$\rightarrow$	$\rightarrow$			
3.7.1	Recovery from stall events in: – take-off configuration; – clean configuration at low altitude; – clean configuration near maximum operating altitude; and – landing configuration.	P FFS qualified for the training task only	X An aero- plane shall not be used for this exercise			
3.7.2	The following upset exercises: – recovery from nose-high at various bank angles; and – recovery from nose-low at various bank angles	P FFS qualified for the training task only	X An aero- plane shall not be used for this exercise			
3.8 Inst	rument flight procedures					
3.8.1	Adherence to departure and arrival routes and ATC instructions	P→	$\rightarrow$		М	
3.8.2	Holding procedures	P→	$\rightarrow$			
3.8.3*	3D operations to DH/A of 200 feet (60 m) or to higher minima of required by approach procedure					
manual limitatio	ly shall be chosen taking into acc n).			require the use of autopilot or flight direct ns (for example, choose an ILS for 3.8.3		
3.8.3.1*	- manually, without flight director	P→	$\rightarrow$		<b>M</b> (skill test only)	
3.8.3.2*	- manually, with flight director	P→	$\rightarrow$			
3.8.3.3*	- with autopilot	P→	$\rightarrow$			

5 (12)



1	Manually, with one engine simulated						
	inoperative during final approach,						
	either until touchdown or through the						
	complete missed approach						
	procedure (as applicable), starting: (i) before passing 1 000 ft						
	above aerodrome level; and						
	(ii) after passing 1 000 ft						
	above aerodrome level.						
	In aeroplanes which are not						
	certificated as transport category						
	aeroplanes (JAR/FAR 25) or as				M choice		
	commuter category aeroplanes				of (i)		
	(SFAR 23), the approach with	_			or (ii)		
	simulated engine failure and the	P→	$\rightarrow$		or both		
	ensuing go- around shall be initiated				or both		
	in conjunction with the 2D approach in accordance with 3.8.4.						
	The go- around shall be initiated						
	when reaching the published						
	obstacle clearance height/altitude						
	(OCH/A); however, not later than						
	reaching an MDH/A of 500 ft above						
	the runway threshold elevation. In						
	aeroplanes having the same						
	performance as a transport category						
	aeroplane regarding take-off mass						
	and density altitude, the instructor						
	may simulate the engine failure in accordance with exercise 3.8.3.4.						
3.8.4*	2D operations						
5.0.4	down to the MDH/A	P*→	$\rightarrow$				
					м		
					141		
To optok	lich ar maintain DPN privilages, one o	pproach al		RND ADCH Where an RND ADCH is not are			
		pproach sł	nall be an l	RNP APCH. Where an RNP APCH is not pra		all be perform	med in an
	lish or maintain PBN privileges, one a ately equipped FSTD.	pproach sl	nall be an l	RNP APCH. Where an RNP APCH is not pra		all be perform	med in an
appropri	ately equipped FSTD.				cticable, it sh	·	
appropri By way o	ately equipped FSTD. of derogation from the subparagraph a	bove, in ca	ases where	RNP APCH. Where an RNP APCH is not pra a proficiency check for revalidation of PBN   P APCH. The restriction shall be lifted if the p	cticable, it sh	es not includ	e an RNP
appropri By way o APCH e check in	ately equipped FSTD. of derogation from the subparagraph a xercise, the PBN privileges of the pilot cluding an RNP APCH exercise.	bove, in ca	ases where	e a proficiency check for revalidation of PBN	cticable, it sh	es not includ	e an RNP
appropri By way o APCH e	ately equipped FSTD. of derogation from the subparagraph a xercise, the PBN privileges of the pilot cluding an RNP APCH exercise. Circling approach under following	bove, in ca	ases where	e a proficiency check for revalidation of PBN	cticable, it sh	es not includ	e an RNP
appropri By way o APCH e check in	ately equipped FSTD. of derogation from the subparagraph a xercise, the PBN privileges of the pilot cluding an RNP APCH exercise. Circling approach under following conditions:	bove, in ca	ases where	e a proficiency check for revalidation of PBN	cticable, it sh	es not includ	e an RNP
appropri By way o APCH e check in	ately equipped FSTD. of derogation from the subparagraph a xercise, the PBN privileges of the pilot cluding an RNP APCH exercise. Circling approach under following conditions: (a) * approach to the authorised	bove, in ca shall not ii	ases where	e a proficiency check for revalidation of PBN	cticable, it sh	es not includ	e an RNP
appropri By way o APCH e check in	ately equipped FSTD. of derogation from the subparagraph a xercise, the PBN privileges of the pilot cluding an RNP APCH exercise. Circling approach under following conditions: (a) * approach to the authorised minimum circling approach altitude at	bove, in ca shall not ii	ases where	e a proficiency check for revalidation of PBN	cticable, it sh	es not includ	e an RNP
appropri By way o APCH e check in	ately equipped FSTD. of derogation from the subparagraph a xercise, the PBN privileges of the pilot cluding an RNP APCH exercise. Circling approach under following conditions: (a) * approach to the authorised minimum circling approach altitude at the aerodrome in question in	bove, in ca shall not ii	ases where	e a proficiency check for revalidation of PBN	cticable, it sh	es not includ	e an RNP
appropri By way o APCH e check in	ately equipped FSTD. of derogation from the subparagraph a xercise, the PBN privileges of the pilot cluding an RNP APCH exercise. Circling approach under following conditions: (a) * approach to the authorised minimum circling approach altitude at the aerodrome in question in accordance with the local instrument	bove, in ca shall not ii	ases where	e a proficiency check for revalidation of PBN	cticable, it sh	es not includ	e an RNP
appropri By way o APCH e check in	ately equipped FSTD. of derogation from the subparagraph a xercise, the PBN privileges of the pilot cluding an RNP APCH exercise. Circling approach under following conditions: (a) * approach to the authorised minimum circling approach altitude at the aerodrome in question in accordance with the local instrument approach facilities in simulated	bove, in ca shall not ii	ases where	e a proficiency check for revalidation of PBN	cticable, it sh	es not includ	e an RNP
appropri By way o APCH e check in	ately equipped FSTD. of derogation from the subparagraph a xercise, the PBN privileges of the pilot cluding an RNP APCH exercise. Circling approach under following conditions: (a) * approach to the authorised minimum circling approach altitude at the aerodrome in question in accordance with the local instrument	bove, in ca shall not ii	ases where	e a proficiency check for revalidation of PBN	cticable, it sh	es not includ	e an RNP
appropri By way o APCH e check in	ately equipped FSTD. of derogation from the subparagraph a xercise, the PBN privileges of the pilot cluding an RNP APCH exercise. Circling approach under following conditions: (a) * approach to the authorised minimum circling approach altitude at the aerodrome in question in accordance with the local instrument approach facilities in simulated instrument flight conditions; followed	bove, in ca shall not ii	ases where	e a proficiency check for revalidation of PBN	cticable, it sh	es not includ	e an RNP
appropri By way o APCH e check in	ately equipped FSTD. of derogation from the subparagraph a xercise, the PBN privileges of the pilot cluding an RNP APCH exercise. Circling approach under following conditions: (a) * approach to the authorised minimum circling approach altitude at the aerodrome in question in accordance with the local instrument approach facilities in simulated instrument flight conditions; followed by (b) circling approach to another runway at least 90° off centreline from final approach used in item a),	bove, in ca shall not ii	ases where	e a proficiency check for revalidation of PBN	cticable, it sh	es not includ	e an RNP
appropri By way o APCH e check in	ately equipped FSTD. of derogation from the subparagraph a xercise, the PBN privileges of the pilot cluding an RNP APCH exercise. Circling approach under following conditions: (a) * approach to the authorised minimum circling approach altitude at the aerodrome in question in accordance with the local instrument approach facilities in simulated instrument flight conditions; followed by (b) circling approach to another runway at least 90° off centreline from final approach used in item a), at the authorised minimum circling	bove, in ca shall not ii	ases where	e a proficiency check for revalidation of PBN	cticable, it sh	es not includ	e an RNP
appropri By way o APCH e check in	ately equipped FSTD. of derogation from the subparagraph a xercise, the PBN privileges of the pilot cluding an RNP APCH exercise. Circling approach under following conditions: (a) * approach to the authorised minimum circling approach altitude at the aerodrome in question in accordance with the local instrument approach facilities in simulated instrument flight conditions; followed by (b) circling approach to another runway at least 90° off centreline from final approach used in item a), at the authorised minimum circling approach altitude;	bove, in ca shall not ii	ases where	e a proficiency check for revalidation of PBN	cticable, it sh	es not includ	e an RNP
appropri By way o APCH e check in	ately equipped FSTD. of derogation from the subparagraph a xercise, the PBN privileges of the pilot cluding an RNP APCH exercise. Circling approach under following conditions: (a) * approach to the authorised minimum circling approach altitude at the aerodrome in question in accordance with the local instrument approach facilities in simulated instrument flight conditions; followed by (b) circling approach to another runway at least 90° off centreline from final approach used in item a), at the authorised minimum circling approach altitude; Remark: if a) and b) are not possible	bove, in ca shall not ii	ases where	e a proficiency check for revalidation of PBN	cticable, it sh	es not includ	e an RNP
appropri By way o APCH e check in	ately equipped FSTD. of derogation from the subparagraph a xercise, the PBN privileges of the pilot cluding an RNP APCH exercise. Circling approach under following conditions: (a) * approach to the authorised minimum circling approach altitude at the aerodrome in question in accordance with the local instrument approach facilities in simulated instrument flight conditions; followed by (b) circling approach to another runway at least 90° off centreline from final approach used in item a), at the authorised minimum circling approach altitude; Remark: if a) and b) are not possible due to ATC reasons a simulated low	bove, in ca shall not ii	ases where	e a proficiency check for revalidation of PBN	cticable, it sh	es not includ	e an RNP
appropri By way of APCH e check in 3.8.5*	ately equipped FSTD. of derogation from the subparagraph a xercise, the PBN privileges of the pilot cluding an RNP APCH exercise. Circling approach under following conditions: (a) * approach to the authorised minimum circling approach altitude at the aerodrome in question in accordance with the local instrument approach facilities in simulated instrument flight conditions; followed by (b) circling approach to another runway at least 90° off centreline from final approach used in item a), at the authorised minimum circling approach altitude; Remark: if a) and b) are not possible due to ATC reasons a simulated low visibility pattern may be performed	bove, in ca shall not in P*→	ases where nclude RN	e a proficiency check for revalidation of PBN	cticable, it sh	es not includ	e an RNP
appropri By way o APCH e check in	ately equipped FSTD. of derogation from the subparagraph a xercise, the PBN privileges of the pilot cluding an RNP APCH exercise. Circling approach under following conditions: (a) * approach to the authorised minimum circling approach altitude at the aerodrome in question in accordance with the local instrument approach facilities in simulated instrument flight conditions; followed by (b) circling approach to another runway at least 90° off centreline from final approach used in item a), at the authorised minimum circling approach altitude; Remark: if a) and b) are not possible due to ATC reasons a simulated low	bove, in ca shall not ii	ases where	e a proficiency check for revalidation of PBN	cticable, it sh	es not includ	e an RNP
appropri By way of APCH e check in 3.8.5*	ately equipped FSTD. of derogation from the subparagraph a xercise, the PBN privileges of the pilot cluding an RNP APCH exercise. Circling approach under following conditions: (a) * approach to the authorised minimum circling approach altitude at the aerodrome in question in accordance with the local instrument approach facilities in simulated instrument flight conditions; followed by (b) circling approach to another runway at least 90° off centreline from final approach used in item a), at the authorised minimum circling approach altitude; Remark: if a) and b) are not possible due to ATC reasons a simulated low visibility pattern may be performed	bove, in ca shall not in P*→	ases where nclude RN	e a proficiency check for revalidation of PBN	cticable, it sh	es not includ	e an RNP
appropri By way of APCH e check in 3.8.5*	ately equipped FSTD. of derogation from the subparagraph a xercise, the PBN privileges of the pilot cluding an RNP APCH exercise. Circling approach under following conditions: (a) * approach to the authorised minimum circling approach altitude at the aerodrome in question in accordance with the local instrument approach facilities in simulated instrument flight conditions; followed by (b) circling approach to another runway at least 90° off centreline from final approach used in item a), at the authorised minimum circling approach altitude; Remark: if a) and b) are not possible due to ATC reasons a simulated low visibility pattern may be performed	bove, in ca shall not in P*→	ases where nclude RN	e a proficiency check for revalidation of PBN P APCH. The restriction shall be lifted if the p	cticable, it sh privileges dou ilot has comp	es not includ oleted a profi	e an RNP



	ON 4 MISSED APPROACH EDURES	FSTD	A	Instructors initials when training completed	Tested or checked in FSTD or A	Pass	Fail
4.1*	Go-around with all engines operating* during a 3D operation on reaching decision height	P*→	$\rightarrow$				
4.2	Go-around with all engines operating* from various stages during an instrument approach	P*→	$\rightarrow$				
4.3	Other missed approach Procedures	P*→	$\rightarrow$				
4.4*	Manual Go-around with the critical engine simulated inoperative after an instrument approach on reaching DH, MDH or MAPt	P*→	→		м		
4.5	Rejected landing with all engines operating: – from various heights below DH/MDH; – after touchdown (baulked landing) In aeroplanes which are not certificated as transport category aeroplanes (JAR/FAR 25) or as commuter category aeroplanes (SFAR 23), the rejected landing with all engines operating shall be initiated below MDH/A or after touchdown.	P→	→				
				Examiners initials when			

test section completed.....

SECT	ION 5 LANDINGS	FSTD	A	Instructors initials when training completed	Tested or checked in FSTD or A	Pass	Fail
5.1	Normal landings* with visual reference established when reaching DA/H following an instrument approach operation	Р					
5.2	Landing with simulated jammed horizontal stabiliser in any out-of-trim position.	P→	An aircraft may not be used for this exercise		FFS only		
5.3	Cross wind landings (a/c, if practicable).	P→	$\rightarrow$				
5.4	Traffic pattern and landing without extended or with partly extended flaps and slats.	P→	$\rightarrow$				
5.5	Landing with critical engine simulated inoperative.	P→	$\rightarrow$		М		
5.6	Landing with two engines inoperative – Aeroplanes with three engines: the centre engine and one outboard engine as far as practicable according to data of the AFM. – Aeroplanes with four engines, two engines at one side.	Ρ	x		M FFS only (skill test only)		
	•			Examiners initials when test section completed			



-	ION 6 ADDITIONAL ORIZATION CAT II/III	FSTD	۲	Instructors initials when training completed	Tested or checked in FSTD or A	Pass	Fail	
less th The fo DH of	General remarks: Special requirements for extension of a type rating for instrument approaches down to a decision height of less than 200 feet (60 m), i.e. Cat II/III operations. The following manoeuvres and procedures are the minimum training requirements to permit instrument approaches down to a DH of less than 60 m (200 ft). During the following instrument approaches and missed approach procedures all aeroplane equipment required for type certification of instrument approaches down to a DH of less than 60 m (200 ft) shall be used.							
6.1*	Rejected take-off at minimum authorised RVR	P*→	→ X An aircraft may not be used for this exercise		М*			
6.2*	CAT II/III Approaches In simulated instrument flight conditions down to the applicable DH, using flight guidance system. Standard procedures of crew coordination (task sharing, call out procedures, mutual surveillance, information exchange and support) shall be observed.	P→	→		М			
6.3*	Go-around after approaches as indicated in 6.2 on reaching DH. The training also shall include a go-around due to (simulated) insufficient RVR, wind shear, aeroplane deviation in excess of approach limits for a successful approach, and ground/airborne equipment failure prior to reaching DH and, go-around with simulated airborne equipment failure	P→	→		M*			
6.4*	Landing(s) with visual reference established at DH following an instrument approach. Depending on the specific flight guidance system, an automatic landing shall be performed	P→	→		М			
NOTE	: CAT II/III operations shall be ac	complish	ied in acc	ordance with Operational Rules.				
				Examiners initials when				
				test section completed				



Н.	Details of the flight								
	Registration of A/C and/or FSTD qualification no	Block on	On ground						
	Departure aerodrome	Block off	Take-off						
	Destination aerodrome	Total block	Total						
	Aeroplane variant	Applicant tested as	PIC						

#### I.

Г

REMARKS		
Item no	Comment	
Of an advance of a service advance of a service of		
Signature of applicant if required		

#### J.

#### ADDITIONAL INFORMATION

#### Κ.

L.

#### ZFTT Simulator training

Six (6) take offs and landings in simulator completed date		FSTD qualification number and level	
Signature of TRI	TRI Name in block lett	ters	TRI Licence number
ZFTT LIFUS training			
Date, sector(s) & signature of TRI(s) (LIFUS)	Name(s) in block letter	rs	TRI(s) (LIFUS) Licence number
AEROPLANE TRAINING			
Aeroplane training completed date	Aircraft type		Numbers of landings/airborne hrs
Signature of TRI	Name in block letters		Licence number



10 (12)

ATPL(A), Type rating multi pilot aeroplane and single pilot complex aeroplanes with high performance, Proficiency check multi pilot aeroplane and single pilot complex aeroplane with high performance,

Instructions for completing form

- A. Please tick the appropriate boxes for relevant test/check. If the PC is conducted for the revalidation of a valid rating, please tick "Revalidate". If the rating has lapsed the applicant must have undergone approved refresher training. See part "F" page 2 in the protocol.
- **B.** Please enter the complete information. "Licence endorsement" means the relevant type of aeroplane according to EASA Class and Type Rating List (Aeroplanes).
- **C.** Personal information of the applicant, always required

The following shall be documented before a Proficiency check;

Total flight time

•

The following shall be checked in the applicant's pilot logbook (conventional or electronic) and documented before a type skilltest

• At least 70 hours PIC (Unless undergoing an MPL training course)

The following shall be checked in the applicant's pilot logbook (conventional or electronic) and documented before an ATPL skilltest

- At least 1500 hours of flight time in aeroplanes
- 500 hours in multi-pilot aeroplanes
- 500 hours as PIC under supervision; or
  - 250 hours as PIC; or
  - 250 hours, including at least 70 hours as PIC, and the remaining as PIC under supervision
- 200 hours of cross-country flight time of which at least 100 hours shall be as PIC or as PIC under supervision
- 75 hours of instrument time of which not more than 30 hours may be instrument ground time
- 100 hours of night flight as PIC or co-pilot
- Out of the 1500 hours of flight time, up to 100 hours of flight time may have been completed in an FFS and FNPT. Of these 100 hours, only a maximum of 25 hours may be completed in an FNPT.

If the applicant states PICUS flight experience, verification is required according to the following: Crediting of Pilot In Command Under Supervision (PICUS) flight time, with the purpose of reaching the requirement for an ATPL skilltest may be recorded as long as it is performed in accordance with AMC1 FCL.050 (b) (5). The Swedish transport agency require a written verification, from a manager such as a chief pilot, NP flight operations, chief flight instructor or equivalent position in the organization that the recording of the PICUS time has been done in accordance with AMC1 FCL.050 (b) (5). The actual recording of the PICUS flight time shall be done in accordance with AMC1 FCL.050 (b) (1) (v).

# AMC1 ARA.GEN.315 Applicant VERIFICATION OF COMPLIANCE By ticking this box you certify that you:

(1) do not hold any personnel licence, certificate, rating, authorisation or attestation

with the same scope and in the same category issued in another Member State;

(2) has not applied for any personnel licence, certificate, rating, authorisation or

attestation with the same scope and in the same category in another Member State; and

(3) has never held any personnel licence, certificate, rating, authorisation or attestation

with the same scope and in the same category issued in another Member State which was

revoked or suspended in any other Member State.

Incorrect information could disqualify you from being granted a personnel licence, certificate, rating, authorization or attestation.

D. This section is to be completed by the Head of Training of the ATO if the purpose is a skill test after basic training or a PC after approved refresher training for the renewal of a lapsed type- or class rating. If the training is performed as an approved zero flight time training course, the head of training must indicate it in the appropriate box.

Applicants who have completed a Part-FCL type rating course at a non-Swedish ATO must attach the following documents to the application:

- Course completion certificate.
- ATO Approval Certificate
- FSTD qualification certificate.
- The Examiners certificate documents including copy of the licence.
- Copy of the licence of the TRI responsible for the aircraft training or LIFUS as applicable.

The result of the test. In case of non-Swedish examiner, the following attachments are required; The Examiners certificate documents including copy of the license

Ε.



11 (12)

F. This section is a checklist with prerequisites for the examiner to check before the test/check. Please mind that a

AUPRT is required according to the table below and a certificate or verification of training/checking must be attached to the application.

First typerating	AUPRT required
MPA→MPA	AUPRT not required (credited)
SP HPA→SP HPA	AUPRT not required (credited)
SP HPA→MPA	AUPRT required
MP MPA→SP HPA	AUPRT required

\* An Advanced UPRT course is not required for a pilot who, within the three preceding years, has completed one of the following;

- all the training and checking items in accordance with points ORO.FC.220 and ORO.FC.230 of Annex III (Part-ORO) to Regulation (EU) No 965/2012 or;
  - completed the training for an AUPRT instructor specified in point FCL.915(e)(1)(ii).

Applicants who wish to convert a third-country type rating into a Part-FCL type rating need to comply with the advanced UPRT prerequisite

# Please note that the examiner must sign and thus affirm that he has checked all prerequisites before the test.

1. The following symbols mean:

P = Trained as Pilot-in-command or Co-pilot and as Pilot Flying (PF) and Pilot Not Flying (PNF) for the issue of a type rating as applicable.

X = Simulators shall be used for this exercise, if available, otherwise an aircraft shall be used if appropriate for the manoeuvre or procedure.

P# = the training shall be complemented by supervised aeroplane inspection

 The practical training shall be conducted at least at the training equipment level shown as (P), but may be conducted up to any higher equipment level shown by the arrow (→).

The following abbreviations are used to indicate the training equipment used:

A = Aeroplane

FFS = Flight Simulator

OTD = Other Training Devices

- 3. The starred items (\*) shall be flown solely by reference to instruments. If this condition is not met during the skill test or proficiency check, the type rating will be restricted to VFR only.
- 4. Where the letter 'M' appears in the skill test/proficiency check column this indicates a mandatory exercise.
- 5. A flight simulator shall be used for practical training and testing if the simulator forms part of an approved typerating course. The following considerations will apply to the approval of the course:
  - a. the qualification of the flight simulator or FNPTII as set out in Part-ORA;
  - b. the qualifications of the instructor and examiner;
  - c. the amount of line-orientated simulator training provided on the course;
  - d. the qualifications and previous line operating experience of the pilot under training; and
  - e. the amount of supervised line flying experience provided after the issue of the new type rating.
- 6. In the case of single-pilot high performance complex aeroplanes, when a skill test or proficiency check is performed in multi-pilot operations, the type rating shall be restricted to multi-pilot operations. If privileges of single-pilot are sought, the manoeuvres/procedures in 2.5, 3.9.3.4, 4.3, 5.5 and at least one manoeuvre/procedure from section 3.4 have to be completed in addition as single-pilot.

G.



7. The following limits shall apply corrected to make allowance for turbulent conditions and the handling qualities and performance of the aeroplane used:

Height:

Generally	±100 feet
Starting a go-around at decision height	+50 feet/-0 feet
Minimum descent height/altitude	+50 feet/-0 feet

#### Tracking:

racking:		
On radio aids	±5°	
For "angular" deviations	Half scale deflection, azimuth and glide path (e.g. LPV, ILS, MLS, GLS)	
2D (LNAV) and 3D (LNAV/VNAV) "linear" deviations	Cross track error/deviation shall normally be limited to $\pm \frac{1}{2}$ the RNP value associated with the procedure. Brief deviations from this standard up to a maximum of 1 time the RNP value are allowed.	
3D linear vertical deviations (e.g. RNP APCH (LNAV/VNAV) using BaroVNAV)	Not more than -75 feet below the vertical profile at any time, and not more than +75 feet above the vertical profile at or below 1000 feet above aerodrome level.	

#### Heading:

riodding.		
	All engines operating	±5°
	With simulated engine failure	±10°
	5	

#### Speed:

All engines operating	±5 knots	
With simulated engine failure	+10 knots/-5 knots	

8. To establish or maintain PBN privileges one approach shall be an RNP APCH. Where an RNP APCH is not practicable, it shall be performed in an appropriately equipped FSTD.

- H. Details of the flight .Please enter the simulator approval number if the test is conducted in a simulator.
- I. Comments regarding the conduct of items.
- J. Additional information regarding the conditions during the test/check. E.g. Staff, weather etc.

K. Specific requirements for pilots undertaking a zero flight time type rating (ZFTT) course – aeroplanes
 (a) A pilot undertaking instruction at a ZFTT course shall have completed, on a multi-pilot turbo-jet aeroplane certificated to the standards of CS-25 or equivalent airworthiness code or on a multi-pilot turbo-prop aeroplane having a maximum certificated take-off mass of not less than 10 tonnes or a certificated passenger seating configuration of more than 19 passengers, at least:

(1) if an FFS qualified to level CG, C or interim C is used during the course, 1 500 hours flight time or 250 route sectors;

(2) if an FFS qualified to level DG or D is used during the course, 500 hours flight time or 100 route sectors.

Details of take-off and landing completed in a qualified FSTD and the number of initial take off and landings as part of a zero flight time training course. Please note that the form shall be submitted to Transportstyrelsen after the completion of the skill test. After completion of the zero flight time training, the completed form shall be submitted again.

L Details of the aeroplane training (landings).